



FIRBESON

F30S Series Spring Return Damper Actuator

The damper actuator specially designed for the air dampers of the HVAC Systems



Torque

3.5Nm, 5Nm, 10Nm, 15Nm, 20Nm

Supply Voltage & Control

AC/DC 19.2-28.8V or AC 85-265V, 2/3 point

AC/DC 19.2-28.8V, 0(2)-10V or 0(4)-20mA

Order code

F30 S - X X X - X

Accessories : S for Auxiliary Switches

Power source : 24 for AC/DC19.2-28.8V;
230 for AC 85-265V

Control : D for 2 point; M for modulating

Torque : 3.5Nm, 5Nm, 10Nm, 15Nm, 20Nm

S for Spring Return

Labeling of Series

5Nm Model Type

Model	Torque	Running Time	Nominal Voltage	Auxiliary Switches
F30S-5D24	5Nm	Motor Running < 70s; Spring Return < 20s (For Modulating Motor Running < 120s; Spring Return < 20s)	AC/DC 24V Or AC 230V	Without
F30S-5D230				With 2 SPDT
F30S-5M24				
F30S-5D24-S				
F30S-5D230-S				
F30S-5M24-S				

F30S-5 Specification

Items	F30S-5D24 F30S-5D24-S	F30S-5D230 F30S-5D230-S	F30S-5M24 F30S-5M24-S
Electrical Parameters			
Nominal Voltage （V）	AC/DC 24V 50/60Hz	AC 230V 50/60Hz	AC/DC 24V 50/60Hz
Nominal Voltage Range （V）	AC/DC19.2-28.8V	AC 85-265V	AC/DC19.2-28.8V
Power Consumption （on）	5W		
Power Consumption （off）	2.5W		
Cable	2 point: 1m cable 3*0.75mm ² ; Modulating: 1m cable 4*0.5mm ² ; Positional Feedback: 1m cable 6*0.5mm ²		
Technical Parameters			
Torque	5Nm		
Damper Area （m ² ）	1		
Running Time	Motor Running < 70s; Spring Return < 20s		Motor < 120s; Spring < 20s
Control Signal	2 point		0(2)-10V
Angle of Rotation	0~90° (max 93°)		
Direction of Rotation	L/R switch		
Positional Feedback	None or 2 SPDT		None or 1 SPDT
Life Cycle	≥70000		
Noise Level	50dB and 62dB		
Operating Condition			
Protection Class	II/III		
Degree of Protection	IP54		
Ambient Temperature	-30~+55℃		
Ambient Humidity	5~95%RH		
Non-operating Temperature	-40~+80℃		
Dimensions & Weight			
Spindle Diameter	 10 - 16 mm		
Weight （Kg）	1.4		
Certificates	CE, UKCA, UL, RoHS		